


## RCCN 日成HC型线槽粘式固定座 Self Adhesive Backed Mounts






单位/Unit:mm

型号 Item No	长 Length L	宽 Wide W	高 High H	螺丝孔 Screw hole B	扎线带穿孔 Hole of cable tie suit to tooth width T	包装 Packing
HC-101	19.5	19.5	3.9	3.2	4.5	100pcs 或 500pcs
HC-102	29	29	6.0	7.0	6.0	
HC-101/3M	19.5	19.5	3.9	3.2	4.5	
HC-102/3M	29	29	6.0	7.0	6.0	


材质：UL合格之NYLON 66(本色),防火等级94V-2。  
用法：使用时将底面胶带撕去封纸,再将固定贴于线槽内,复以日成扎线带于孔中,即可使用,可省去面板钻孔之麻烦。

备注：背胶采用进口双面胶,粘性牢.HC-101/3M为3M背胶,适合环境要求较高。

\*Available in either "screw mount" or "self adhesive mounting". This range offers a safe and secure mount.  
\*Simple to install with a screw or bolt, the tie mounts give excellent security, particularly in areas of high vibration.  
\*Designed to offer the maximum surface area, and in conjunction with the specially developed adhesive ensures that a very high pull-off force is achieved.  
\*The tie mounts offer a '4-way' entry for the cable tie enabling quicker and more flexible installation.  
\*Material: Polyamide 6.6, UL94 V2



## RCCN 日成HC型扎线固定座 Saddle Tie Mounts




单位/Unit:mm

型号 Item No	长 Length L	宽 Wide W	高 High H	螺丝孔 Screw hole B	扎线带穿孔 Hole of cable tie suit to tooth width T	包装 Packing
HC-1	15.0	10.0	7.0	3.3	5.1	100pcs
HC-2	20.5	17.1	10.4	5.0	10.4	

材质：UL合格之NYLON 66(本色),防火等级94V-2。  
用途：先将固定座置于槽内以螺丝或铆钉固定再以扎线带绕绑电缆。  
根据捆线范围选择合适扎带长度,参考日成扎带型号。



Material: UL approved NYLON 66(natural), fireproof 94V-2.  
Function: fix mount inside the duct, then bundle wires with cable tie, choose cable tie size according to RCCN's catalogue



本品可用于固定线槽配件用  
This items can be used to fix duct accessories

## RCCN 日成线槽连接件 Duct Corner/Joining Strips

单位/Unit:mm



型号 Item No.				长度 Length L	适合线槽高度 Suitable wiring duct height H	包装 Packing
灰色 Gray	白色 White	蓝色 Blue	黑色 Black			
DCS-30	DCS-30W	DCS-30E	DCS-30B	20	30	20
DCS-40	DCS-40W	DCS-40E	DCS-40B	30	40	20
DCS-50	DCS-50W	DCS-50E	DCS-50B	40	50	20
DCS-60	DCS-60W	DCS-60E	DCS-60B	50	60	20
DCS-80	DCS-80W	DCS-80E	DCS-80B	70	80	10
DCS-100	DCS-100W	DCS-100E	DCS-100B	90	100	10
DJS-30	DJS-30W	DJS-30E	DJS-30B	20	30	20
DJS-40	DJS-40W	DJS-40E	DJS-40B	30	40	20
DJS-50	DJS-50W	DJS-50E	DJS-50B	40	50	20
DJS-60	DJS-60W	DJS-60E	DJS-60B	50	60	20
DJS-80	DJS-80W	DJS-80E	DJS-80B	70	80	10
DJS-100	DJS-100W	DJS-100E	DJS-100B	90	100	10

产品材质:采用低卤素硬质PVC料制成,环保无污染,不含铅等有毒物。  
用途：用于线槽并接或直角末端保护,防电线刮伤。

Material:Low Halogen rigid PVC,lead free environment-friendly  
Use : connect wiring duct,

其它规格来电询问